



Material Safety Data Sheet

Occupational Safety and Health Administration, (Non-Mandatory Form), Form Approved OMB No. 1218-0072

The information in this MSDS was obtained from current and reputable sources. However, the data provided is without warranty, expressed or implied, regarding its correctness or accuracy. It is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury damage or expense resulting from improper use of this product.

IDENTITY: EST AUTOMATIC TRANSMISSION FLUID CONDITIONER AND SEALER #2520	Health: 1 Fire: 1 React: 0 PPE: Gloves, Safety Glasses
Product Description: Automatic Transmission Fluid Additive and Stop Leak	Hazard Rating System (NFPA) 0 = Minimal 1 = Slight 2 = Moderate 3 = High 4 = Extreme

Section I - Identification

Manufacturer's Name: EnviroLution	Emergency Telephone Number: 818 256-2355
Address: 511 Fifth Street, San Fernando, CA 91340	Telephone Number for Information: 818 256-2379
	Date Prepared: Jan 2004

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	Cas No.	% (optional)	OSHA PEL	ACGIH TLV	Other Limits Recommended
Petroleum				5MG/3M	
Fatty Esters	Mixture				
Proprietary Material					

Section III - Physical/Chemical Characteristics

Boiling Point	> 400 F.	Specific Gravity (H₂O = 1)	0.86 – 0.88
Freezing Point	Not applicable	pH	Not applicable
Vapor Pressure (mm Hg @ 20 C.)	> 1	% Volatile	0
Vapor Density (AIR = 1)	> 1	Melting Point	Not applicable
Solubility in Water	Insoluble	Evaporation Rate (Butyl Acetate = 1)	Not applicable
Appearance and Odor	Red liquid with oil odor		

**EST AUTOMATIC TRANSMISSION FLUID
CONDITIONER AND SEALER #2520**



Material Safety Data Sheet

Occupational Safety and Health Administration, (Non-Mandatory Form), Form Approved OMB No. 1218-0072

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used):	< 350 F. (TCC)	Flammable Limits: N/A	LEL: N/A	UEL: N/A
Extinguishing Media:	Water Fog, Alcohol Foam, Carbon Dioxide, Dry Chemical. DO NOT use straight water streams.			
Special Fire Fighting Procedures:	Wear approved SCBA with full-face piece operated in the positive pressure demand mode to protect against hazardous effect of normal products of combustion or oxygen deficiency.			
Hazardous Combustion:	Burning generates carbon monoxide, carbon dioxide unidentified organic compounds and smoke.			
Unusual Fire and Explosion Hazards:	Material will not burn unless preheated. Material will float and can be re-ignited on surface of water.			

Section V - Reactivity Data

Stability	Unstable		Conditions to avoid
	Stable	X	
Incompatibility (Materials to Avoid):	Avoid oxidizing agents.		
Hazardous Decomposition or Byproducts:	Burning generates carbon monoxide, carbon dioxide and smoke.		
Hazardous Polymerization	May Occur		Conditions to avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (Acute and Chronic) Skin Contact – See below. Eye Contact – See below. Ingestion – See below. Inhalation – See below.			
Carcinogenicity: No	NTP? No	IARC Monographs? No	OSHA Regulated? No.
Signs and Symptoms of Exposure: Skin Contact – Lubricating oils are generally considered no more than minimally irritating to the skin. Prolonged and repeated contact may result in defatting and drying of the skin that may cause various skin disorders such as dermatitis, folliculitis or oil acne. Eye Contact – Lubricating oils are generally considered no more than minimally irritating to the eyes. Ingestion – Lubricating oils are generally considered no more than slightly toxic if swallowed, Inhalation – Inhalation of vapors (generated at high temperatures only) or oil mist may cause mild irritation of the nose, throat, and respiratory tract.			
Medical Conditions Generally Aggravated by Exposure: None currently none.			
Emergency and First Aid Procedures: Skin Contact – Wash affected area with soap and water and remove contaminated clothing. Get medical attention if irritation persists. Eyes – Immediately flush with water for at least 15 minutes while holding the eyelids apart and away from the eyeballs			

**EST AUTOMATIC TRANSMISSION FLUID
CONDITIONER AND SEALER #2520**



Material Safety Data Sheet

Occupational Safety and Health Administration, (Non-Mandatory Form), Form Approved OMB No. 1218-0072

during flushing. Seek medical attention if irritation occurs.

Ingestion – DO NOT INDUCE vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention.

Inhalation – Move to fresh air. If breathing is difficult, administer oxygen until the victim is able to breathe on his or her own without difficulty. Seek medical attention.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled: Do not allow to enter waterways. Contain and collect with absorbent. Product may burn though not readily ignitable.

Waste Disposal Method: Dispose of in accordance with local, state, and federal laws.

Precautions to Be taken in Handling: Do not get on eyes, skin or clothes.

Precautions to Be taken in Storage: None

Special Shipping Instructions: None

Other Precautions: Keep away from open flame and high temperatures.

Section VIII - Control Measures

Respiratory Protection (*Specify Type*): None required for normal use.

Ventilation

Local Exhaust: N/A

Special: N/A

Mechanical (*General*): N/A

Other: Normal air circulation.

Protective Gloves: Nitrile/Vinyl/Rubber

Eye Protection: Glasses/Goggles (Recommended). Contact lens should not worn when working with this product.

Other Protective Clothing or Equipment: Coveralls/Apron

Work/Hygienic Practices: Always wash you hands after handling chemicals. Never wear contaminated clothing.

Section IX – Other Information

Clean Water Act: This product is an oil as defined under Section 311 of EPA's Clean Water Act (CW:A). Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center, 1-800-424-8802.

EnviroLution makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by EnviroLution as to the effects of such use, the results to be obtained or the safety and toxicity of this product referred to herein. The data in this MSDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.



Material Safety Data Sheet

Occupational Safety and Health Administration, (Non-Mandatory Form), Form Approved OMB No. 1218-0072

***EST AUTOMATIC TRANSMISSION FLUID
CONDITIONER AND SEALER #2520***