

Concrete Form Oil Form Release Agent

DESCRIPTION: Concrete Form Oil is light colored non-staining oil for use on concrete forms.

QUALITIES: This oil is specially compounded with a combination spreading and release agent. Its use provides even spreading of the oil on wood or steel forms and prevents the cement from sticking to the forms.

PREVENTS DISCOLORATION: Concrete Form Oil is formulated with high quality base stocks and additives selected to prevent discoloration of the cement being formed.

REMOVES EASILY: This product can be easily removed from forms with water. Its formulation prevents staining, build-up or corrosion of the forms.

USED FOR SPECIAL APPLICATIONS: Concrete Form Oil may be diluted for special applications with up to 3:1 parts No. 1 fuel oil for spraying on both steel and wood. No staining has been experienced with this dilution.

APPLICATIONS: Concrete Form Oil may be used for all concrete form applications. Due to its excellent non-staining characteristics, major users include burial vault manufacturers and white stone furniture fabricators.

PROPERTIES/TYPICAL VALUES:	CONCRETE FORM OIL
Gravity, °API	22.7
Flash Point, °F (°C)	310 (164)
Viscosity, cSt at 40°C	23.0 – 29.1
Viscosity, cSt at 100°C	4.7
Viscosity, SUS at 100°F	120 – 150
Viscosity, SUS at 210°F	42
Pour Point, °F (°C)	-35 (-37)
Color, ASTM D 1500	3
Saponification Number	12
Pounds Per Gallon	7.64