

**CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** Hartland Base Oil 110, 120, 150, 250, 300  
**PRODUCT USE/CLASS:** Oil Based Products  
**EMERGENCY:** PROFESSIONAL EMERGENCY RESOURCE SERVICES  
 24 HOUR (PERS) 1-800-633-8253

**DISTRIBUTOR:** Hartland Lubricants & Chemicals  
 914 Commercial Court  
 Onalaska, WI 54650  
 608-779-6353 / 800-658-9051  
 www.hartlandlubes.com

**REVISION DATE:** February 1, 2012

**SUBSTANCE IDENTIFICATION**

**Identity:** 110 Neutral Base Oil: 110 Neutral Oil  
 120 Neutral Base Oil: 120 Neutral Oil  
 150 Neutral Base Oil: 150 Neutral Oil  
 250 Neutral Base Oil: 250 Neutral Oil  
 300 Neutral Base Oil: 300 Neutral Oil

**CAS Number:** 64742-50-3

**Synonym / Trade Names:** Neutral Oil; HVI Paraffinic, Petroleum Oil  
**Family / Chemical Name:** Re-Refined, Clay-Treated Hydrocarbon, Petroleum  
 Re-Refined, Lubricating Oil

**NFPF Ratings (Scale 0-4):** 0-Health, 1-Fire, 0-Reactivity

**HAZARDOUS INGREDIENTS**

This product fits the ACGIH Definition for Mineral Oil Mist.

Petroleum Hydrocarbon – As Mist / Percent: 100

Exposure Limits in Air

OSHA PEL TWA 5 MG / M3  
 OSHA PEL STEL None Established  
 ACGIH TLV TWA 5 MG / M3  
 ACGIH TLV STEL 10 MB / M3  
 CAL OSHA TWA 5 MG / M3

**PHYSICAL PROPERTIES**

Vapor Density	>1 (Air = 1)	Melting Point	Not Applicable
Specific Gravity	0.85 to 0.88 @ 60°F	Boiling Point	Above 600°F (316°C)
Solubility in Water	Insoluble	Evaporation Rate	<1 (Ether =1)
Vapor Pressure	<0.001 MM HG@ 20°C	% Volatile	Negligible
Density	7.1 Lbs / Gallon	PH	Not Applicable
Coefficient of Water/Oil Distribution	N/A	Pour Point	-15°F
Molecular Weight	>400	API Gravity	30 to 33 °API @ 60°F

How to detect this substance: Viscous, oily, amber colored liquid, with a characteristic petroleum odor and slippery feel.

**FIRE AND EXPLOSION DATA**

Flash Point: >360 °F (182 °C) COC

Auto ignition Temp: N/A

Lower Flammable Limit: N/A

Upper Flammable Limit: N/A

Extinguishing Media: Carbon Dioxide, Foam, Dry Chemical

**FIRE FIGHTING PROCEDURES**

Withdraw immediately in case of rising sound from venting safety device or discoloration of tank due to fire. Keep storage containers cool with water spray, use self-contained breathing apparatus (SCBA).

NFPA 704 Rating: (0-Least, 4=Extreme) Health=0, Fire=1, Reactivity=0

**HEALTH HAZARD INFORMATION**

**SYMPTOMS OF EXPOSURE**

**ACUTE**

**INHALED:** HIGH CONCENTRATIONS OF VAPOR OR MIST MAY BE IRRITATING TO THE RESPIRATORY TRACT, INCLUDING NOSE AND THROAT. MAY CAUSE DIFFICULTY BREATHING.

**SKIN:** THIS MATERIAL MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING, AND DERMATITIS. CONTACT WITH HOT MATERIAL MAY CAUSE THERMAL BURNS.

**EYES:** CONTACT MAY CAUSE SLIGHT TO MODERATE IRRITATION, INCLUDING BURNING, TEARING, AND REDNESS. CONTACT WITH HOT MATERIAL MAY CAUSE THERMAL BURNS.

**SWALLOWING (INGESTION):** MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT, NAUSEA AND VOMITING. ASPIRATION INTO THE LUNGS DURING INGESTION OR VOMITING MAY CAUSE MILD TO SEVERE PULMONARY INJURY AND POSSIBLY DEATH.

**CHRONIC**

PROLONGED AND/OR REPEATED SKIN CONTACT MAY CAUSE DRYING AND CRACKING OR DERMATITIS. EXPOSURE TO HIGH OIL MIST CONCENTRATIONS MAY LEAD TO OIL PNEUMONIA.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

CONTACT WITH SKIN MAY AGGRAVATE PRE-EXISTING DERMATITIS.

**CARCINOGENICITY**

NO INGREDIENTS OF THIS PRODUCT, PRESENT AT EQUAL TO OR GREATER THAN 0.1% OF THE PRODUCT, ARE LISTED BY OSHA, NTP OR IARC AS SUSPECTED CARCINOGENS.

**EMERGENCY AND FIRST AID PROCEDURES**

**INHALED (BREATHING):** REMOVE TO FRESH AIR IMMEDIATELY. IF THERE IS DIFFICULTY BREATHING OR IF BREATHING HAS STOPPED, OXYGEN OR ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. DO NOT LEAVE VICTIM UNATTENDED. SEEK IMMEDIATE MEDICAL ATTENTION IF NECESSARY.

**SKIN:** REMOVE CONTAMINATED CLOTHING AND SHOES. DO NOT USE GASOLINE, THINNERS OR SOLVENTS TO REMOVE PRODUCT FROM SKIN. WIPE MATERIAL FROM SKIN AND WASH THOROUGHLY WITH SOAP AND WATER, AND IF NECESSARY A WATERLESS SKIN CLEANSER. CONSULT PHYSICIAN IF IRRITATION OR PAIN PERSISTS.

**EYES:** FOR DIRECT CONTACT, FLUSH EYES WITH WATER FOR 15 MINUTES LIFTING UPPER AND LOWER LIDS OCCASIONALLY. CONSULT PHYSICIAN IF IRRITATION OR PAIN PERSISTS.

**SWALLOWING (INGESTION): DO NOT INDUCE VOMITING,** BECAUSE MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE DAMAGE. DRINK 4 TO 8 OUNCES OF WATER AND SEEK IMMEDIATE MEDICAL ATTENTION. IF VOMITING OCCURS, OR IF COMATOSE OR LETHARGIC, PLACE ON THE LEFT SIDE WITH THE HEAD DOWN - SEEK IMMEDIATE MEDICAL ATTENTION.

**NOTE TO PHYSICIAN:** ADMINISTRATION OF GASTRIC LAVAGE, IF WARRANTED, SHOULD BE PERFORMED BY QUALIFIED MEDICAL PERSONNEL.

**REACTIVITY DATA**

**STABILITY:** STABLE, NOT REACTIVE WITH WATER.

**INCOMPATIBILITY:** MAY REACT WITH STRONG OXIDIZING AGENTS, SUCH AS; CHLORATES, NITRATES AND PEROXIDES. AVOID HEAT, SPARKS, AND FLAMES.

**HAZARDOUS POLYMERIZATION:** NOT KNOWN TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

**HAZARDOUS DECOMPOSITION:** NO DECOMPOSITION PRODUCTS UNDER NORMAL PRODUCT CONDITIONS

**SPECIAL PRECAUTIONS:** READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL. DO NOT WELD, HEAT OR DRILL CONTAINER. RESIDUE MAY IGNITE WITH EXPLOSIVE VIOLENCE IF HEATED SUFFICIENTLY.

**CAUTION:** DO NOT USE PRESSURE TO EMPTY DRUM OR EXPLOSION MAY RESULT.

**SPILL, LEAK, AND DISPOSAL PROCEDURES**

**SPILL PROCEDURE:** REMOVE ALL IGNITION SOURCES, AND AVOID BREATHING VAPORS. VENTILATE AREA IF CONFINED. CONTAIN AS A LIQUID FOR POSSIBLE RE-REFINING IF POSSIBLE BY DIKING AROUND OIL WITH A SUITABLE MATERIAL. IF NOT, ABSORB SPILLED LIQUID IN SAND OR INERT ABSORBENT. CONTAIN AWAY FROM SURFACE WATERS AND SEWERS. SHOVEL INTO CLOSABLE CONTAINER FOR DISPOSAL. CONTACT THE COAST GUARD NATIONAL RESPONSE CENTER (800) 424-8802 IF A SPILL OF ANY AMOUNT IS MADE INTO OR UPON U.S. NAVIGABLE WATERS, THE CONTIGUOUS ZONE, OR ADJOINING SHORELINES.

**WASTE DISPOSAL METHODS:** DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, COUNTY, AND LOCAL REGULATIONS. CONTACT COMO LUBE & SUPPLIES, INC. REGARDING RECYCLING OR DISPOSAL.

**SPECIAL HANDLING INFORMATION**

**VENTILATION AND HANDLING PRECAUTIONS:** KEEP AWAY FROM HEAT, SPARKS AND FLAMES. AVOID CONTACT WITH EYES AND SKIN, AND AVOID BREATHING VAPORS OR MISTS. AVOID GENERATING OIL MISTS.

**RESPIRATORY PROTECTION:** WHEN AIRBORNE CONCENTRATIONS EXCEED RECOMMENDED EXPOSURE LIMITS, A MSHA/NIOSH APPROVED RESPIRATORY PROTECTIVE EQUIPMENT SHOULD BE WORN, SUCH AS AN ORGANIC VAPOR FILTER RESPIRATOR. A SELF-CONTAINED BREATHING APPARATUS (SCBA) IS REQUIRED FOR FIRE EMERGENCIES.

**EYE PROTECTION:** WHERE THERE IS A LIKELIHOOD OF A SPILL OR SPLASH, WEAR CHEMICAL GOGGLES AND FACE SHIELD. CONTACT LENSES SHOULD NOT BE WORN.

**HAND PROTECTION:** USE LATEX, NEOPRENE, NITRILE RUBBER, OR EQUIVALENT GLOVES TO PREVENT CONTACT WITH THE SKIN. BARRIER CREAMS THAT ARE SPECIFIC FOR OIL-BASED MATERIALS ARE RECOMMENDED WHEN GLOVES ARE IMPRACTICAL.

**OTHER PROTECTIVE CLOTHING:** WEAR APPROPRIATE BOOTS, COVERALLS OR OTHER PROTECTIVE CLOTHING WHERE SPILLS AND SPLASHES ARE POSSIBLE. A SOURCE OF CLEAN WATER SHOULD BE AVAILABLE IN WORK AREAS FOR FLUSHING THE EYES AND SKIN IF NECESSARY.

**STORAGE:** STORE IN A COOL, DRY LOCATION. KEEP AWAY FROM INCOMPATIBLE MATERIALS. KEEP CONTAINER TIGHTLY CLOSED. EMPTY PRODUCT CONTAINERS MAY CONTAIN PRODUCT RESIDUE. DO NOT PRESSURIZE, CUT, HEAT, WELD, OR EXPOSE CONTAINERS TO FLAME OR OTHER SOURCES OF IGNITION.

### TRANSPORTATION AND OTHER REGULATORY INFORMATION

**DOT SHIPPING NAME:** LIGHT NEUTRAL, MEDIUM NEUTRAL  
**DOT ID NUMBER:** NOT APPLICABLE  
**DOT CLASS:** NOT APPLICABLE  
**TSCA:** COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY

**SARA TITLE III:** PRODUCT DOES NOT CONTAIN TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND RE AUTHORIZATION ACT OF 1986 AND 40 CFR PART 372.

#### SECTION 311 CATEGORIES:

IMMEDIATE (ACUTE) HEALTH EFFECT:	YES
DELAYED (CHRONIC) HEALTH EFFECTS:	NO
FIRE HAZARD:	NO
SUDDEN RELEASE OF PRESSURE HAZARD:	NO
REACTIVITY HAZARD:	NO

**CALIFORNIA PROP 65:** THIS PRODUCT MAY CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. (SEE ALSO THE HEALTH HAZARD INFORMATION SECTION).

### Disclaimer of Liability

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal to the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable. This MSDS replaces all previous versions for this product. Please discard all previous versions as they may contain changed or obsolete information.

<END OF MSDS>